


4 DELİKLİ SAE C TANDEM DİŞLİ POMPA



HİDROLİK SEMBOL
HYDRAULIC SYMBOL

Fluid	Mineral or synthetic compatible with the following seals: NBR, FKM, FPM, Nylon				
Kinematic viscosity suggested	Average ambient temp. (°C)	< -10	-10÷-10	10÷35	> 35
	VG (cSt = mm ² /s)	22	32	46	68
Optimale kinematic viscosity		VG= 10 cSt ÷ 100 cSt			
Max kinematic viscosity suggested at the start-up		VG= 750 cSt			
Viscosity index suggested	VI > 100	Working temperature -15°C ÷ 100°C			
Oil filtering		> 200 bar: 10 µm < 200 bar: 25 µm			
Inlet pressure		-0,3 ÷ 2 bar			



İletim Hacmi Displacement	Maks. Sürekli Basınç Max. Continuous Pressure	Maks. Aralıklı Basınç Max. Intermittent pressure	Maks. Anlık Basınç Max. Peak Pressure	Maks. Sürekli Hız Max. Continuous speed	Maks. Aralıklı Hız Max. Intermittent speed	Min. Hız Min. speed	A	A1	B	B1	C	C1
(cm ³ /rev)	(100%)(BAR)	(20 sec.max)(BAR)	(6 sec.max)(BAR)	(RPM)	(RPM)	(RPM)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
38	250	270	280	1500	2500	300	-	-	-	-	157.5	90.5
55							177.5	106	167	95.5		
58							178.5	108	168	97.5		
70							187.5	113.5	177	103		
85	230	250	270				193.5	116.5	183	106	174.5	106
100												

İletim Hacmi Displacement	Giriş Inlet				Çıkış Outlet			
(cm³/rev)	C	D	E	F	C	D	E	F
38	52.5	26	M10	25.4	47.6	22	M10	19
55	70	36	M12	38	58.5	30		32
58								
70								
85								
100	78	43		51				