




4 DELİKLİ ASAE-S DİŞLİ POMPA



HİDROLİK SEMBOL
HYDRAULIC SYMBOL

Fluid	Mineral or synthetic compatible with the following seals: NBR, FKM, FPM, Nylon			
Kinematic viscosity suggested	Average ambient temp. (°C)	< -10	-10-10	10-35
	VG (cSt = mm²/s)	22	32	46
Optimale kinematic viscosity		VG= 10 cSt ÷ 100 cSt		
Max kinematic viscosity suggested at the start-up		VG= 750 cSt		
Viscosity index suggested	VI > 100	Working temperature -15°C +100°C		
Oil filtering		> 200 bar: 10 µm < 200 bar: 25 µm		
Inlet pressure		-0,3 ÷ 2 bar		



Kod Code		İletim hacmi Displacement	Max. Sürekli Basıncı Max. Continuous pressure	Maks. Aralıklı Basıncı Max. Intermittent Pressure	Maks. Anlık Basıncı Max. Peak Pressure	Maks. Sürekli Hız Max. Continuous Speed	Maks. Aralıklı Hız Max. Intermittent Speed	Min. Hız Min. Speed	A	B	Giriş Inlet	Çıkış Outlet
Sol/Left	Sağ/Right	(cm³/rev)	(100%)(BAR)	(20 sec.max)(BAR)	(6 sec.max)(BAR)	(RPM)	(RPM)	RPM	(mm)	(mm)	C	D
G300175F211	G300175F221	17	290	315	325	2500	3000	300	173	124.5	G1/2"	G1/2"
G300225F211	G300225F221	22							177	126	G3/4"	
G300275F211	G300275F221	27							179	129.5		
G300345F211	G300345F221	34	280	300	310	2200	2800		184	130.5	G1"	G3/4"
G300435F211	G300435F221	43	270	290	300	2000	190		135.5			
G300515F211	G300515F221	51	240	260	280		195		135.5			
G300615F211	G300615F221	61	220	240	250	1900	205		142	G1 1/4"	G1"	
G300735F211	G300735F221	73	205	225	230		208		144.5			
G300825F211	G300825F221	82					214		146			
G301005F211	G301005F221	100	180	200	220	1500	1800		227	160	G1 1/4"	G1" G3/4" (Alternative)
G301255F211	G301255F221	125	160	180	200				243	164		