




2+4 DELİKLİ SAE B TEK YÖNLÜ KAMALI DIŞLI POMPA


 HİDROLİK SEMBOL
 HYDRAULIC SYMBOL


Fluid	Mineral or synthetic compatible with the following seals: NBR, FKM, FPM, Nylon				
Kinematic viscosity suggested	Average ambient temp. (°C)	< -10	-10-10	10-35	> 35
	VG (cSt = mm²/s)	22	32	46	68
Optimale kinematic viscosity		VG= 10 cSt ÷ 100 cSt			
Max kinematic viscosity suggested at the start-up		VG= 750 cSt			
Viscosity index suggested	VI > 100	Working temperature -15°C +100°C			
Oil filtering		> 200 bar: 10 µm < 200 bar: 25 µm			
Inlet pressure		-0,3 ÷ 2 bar			



Kod Code		İletim hacmi Displacement	Max. Sürekli Basıncı Max. Continuous pressure	Maks. Aralıklı Basıncı Max. Intermittent Pressure	Maks. Anlık Basıncı Max. Peak Pressure	Maks. Sürekli Hız Max. Continuous Speed	Maks. Aralıklı Hız Max. Intermittent Speed	Min. Hız Min. Speed	A	B	Sol/Left- Sağ/Right	
											Giriş Inlet	Çıkış Outlet
Sol/Left	Sağ/Right	(cm³/rev)	(100%)(BAR)	(20 sec.max)(BAR)	(6 sec.max)(BAR)	(RPM)	(RPM)	RPM	(mm)	(mm)	C	D
G30027BK218	G30027BK228	27	290	315	325	2500	3000	300	166	118	G3/4"	G1/2"
G30034BK218	G30034BK228	34	280	300	310	2200	2800		171	123		G3/4"
G30038BK218	G30038BK228	38							174	126		
G30043BK218	G30043BK228	43	270	290	300	2000	2500		177	129	G1"	
G30051BK218	G30051BK228	51	240	260	280				182	126		
G30055BK218	G30055BK228	55	230	250	275				185	130		
G30061BK218	G30061BK228	61	220	240	250				1900	188	133	
G30073BK218	G30073BK228	73	205	225	230	1900			196	141	G1 1/4"	G1"