


4 DELİKLİ TRC ÇİFT YÖNLÜ DİŞLİ POMPA



HİDROLİK SEMBOL
HYDRAULIC SYMBOL

Fluid	Mineral or synthetic compatible with the following seals: NBR, FKM, FPM, Nylon			
Kinematic viscosity suggested	Average ambient temp. (°C)	< -10	-10~10	10~35
	VG (cSt = mm²/s)	22	32	46
Optimale kinematic viscosity		VG= 10 cSt ~ 100 cSt		
Max kinematic viscosity suggested at the start-up		VG= 750 cSt		
Viscosity index suggested	VI > 100	Working temperature -15°C ~100°C		
Oil filtering		> 200 bar: 10 µm < 200 bar: 25 µm		
Inlet pressure		-0,3 ~ 2 bar		



Kod Code	İletim hacmi Displacement	Max. Sürekli Basıncı Max. Continuous pressure	Maks. Aralıklı Basıncı Max. Intermittent Pressure	Maks. Anlık Basıncı Max. Peak Pressure	Maks. Sürekli Hız Max. Continuous Speed	Maks. Aralıklı Hız Max. Intermittent Speed	Min. Hız Min. Speed	A	B	Giriş Inlet	Çıkış Outlet
BD	(cm³/rev)	(100%)(BAR)	(20 sec.max)(BAR)	(6 sec.max)(BAR)	(RPM)	(RPM)	RPM	(mm)	(mm)	C	C
G300175F331	17	290	315	325	2500	3000	300	173	124.5	G1/2"	G1/2"
G300225F331	22							177	126		
G300275F331	27							179	129.5		
G300345F331	34	280	300	310	2200	2800		184	130.5	G3/4"	G3/4"
G300435F331	43	270	290	300	2000	2500		190	135.5		
G300515F331	51	240	260	280				195	135.5		
G300615F331	61	220	240	250	1900	2500		205	142	G1"	G1"
G300735F331	73	205	225	230				208	144.5		
G300825F331	82							214	146		
G301005F331	100	180	200	220	1500	1800	227	160	G1 1/4"	G1 1/4"	
G301255F331	125	160	180	200			243	164			