


4 DELİKLİ ISO TANDEM DİŞLİ POMPA


 HİDROLİK SEMBOL
 HYDRAULIC SYMBOL


Fluid	Mineral or synthetic compatible with the following seals: NBR, FKM, FPM, Nylon				
Kinematic viscosity suggested	Average ambient temp. (°C)	< -10	-10-10	10-35	> 35
	VG (cSt = mm2/s)	22	32	46	68
Optimale kinematic viscosity			VG= 10 cSt + 100 cSt		
Max kinematic viscosity suggested at the start-up			VG= 750 cSt		
Viscosity index suggested	VI > 100	Working temperature		-15°C +100°C	
Oil filtering			> 200 bar: 10 µm < 200 bar: 25 µm		
Inlet pressure			-0.3 - 2 bar		



Kod Code	İletim hacmi Displacement	Max. Sürekli Basıncı Max. Continuous pressure	Maks. Aralıklı Basıncı Max. Intermittent Pressure	Maks. Anlık Basıncı Max. Peak Pressure	Maks. Sürekli Hız Max. Continu- ous Speed	Maks. Aralıklı Hız Max.Intermit- tent Speed	Min. Hız Min. Speed	A	B	Giriş Inlet	Çıkış Outlet
BD	(cm³/rev)	(100%)(BAR)	(20 sec.max)(BAR)	(6 sec.max)(BAR)	(RPM)	(RPM)	(RPM)	(mm)	(mm)	C	C
GT30017SF131	17	290	315	325	2500	3000	300	182.5	123.5	G1/2"	G1/2"
GT30022SF131	22							186.5	126.5		
GT30027SF131	27							188.5	126.5		
GT30034SF131	34	280	300	310	2200	2800		193.5	128.5	G3/4"	G3/4"
GT30036SF131	36							193.5	128.5		
GT30038SF131	38							193.5	128.5		
GT30043SF131	43	270	290	300	2000	2500		199.5	133	G1"	G1"
GT30051SF131	51	240	260	280				204.5	134.5		
GT30061SF131	61	220	240	250	1800	2000		212.5	138.5		
GT30073SF131	73	200	220	230	1600	1800		217.5	141		
GT30082SF131	82	190	210	220	1500			223.5	146		
GT30100SF131	100	180	200	220				236.5	160		
GT30125SF131	125	160	180	200				252.5	164		