




3 DELİKLİ UNI TANDEM DİŞLİ POMPA



HİDROLİK SEMBOL
HYDRAULIC SYMBOL

Fluid	Mineral or synthetic compatible with the following seals: NBR, FKM, FPM, Nylon			
Kinematic viscosity suggested	Average ambient temp. (°C)	< -10	-10-10	10-35
	VG (cSt = mm ² /s)	22	32	46
Optimale kinematic viscosity		VG= 10 cSt ÷ 100 cSt		
Max kinematic viscosity suggested at the start-up		VG= 750 cSt		
Viscosity index suggested	VI > 100	Working temperature -15°C +100°C		
Oil filtering		> 200 bar: 10 µm < 200 bar: 25 µm		
Inlet pressure		-0,3 ÷ 2 bar		



Kod Code	İletim hacmi Displacement	Max. Sürekli Basıncı Max. Continuous pressure	Maks. Aralıklı Basıncı Max. Intermittent Pressure	Maks. Anlık Basıncı Max. Peak Pressure	Maks. Sürekli Hız Max. Continu- ous Speed	Maks. Aralıklı Hız Max.Intermit- tent Speed	Min. Hız Min. Speed	A	B	Giriş Inlet	Çıkış Outlet
BD	(cm³/rev)	(100%)(BAR)	(20 sec.max)(BAR)	(6 sec.max)(BAR)	(RPM)	(RPM)	(RPM)	(mm)	(mm)	Ç	Ç
GT30017UF431	17	290	315	325	2500	3000	300	161	102	G1/2"	G1/2"
GT30022UF431	22							165	104		
GT30027UF431	27							167	104		
GT30034UF431	34	280	300	310	2200	2800		172	106	G3/4"	G3/4"
GT30036UF431	36							172	106		
GT30038UF431	38							172	106		
GT30043UF431	43	270	290	300	2000	2500		178	111,5	G1"	G1"
GT30051UF431	51	240	260	280				183	113		
GT30061UF431	61	220	240	250	1800	2000		191	117		
GT30073UF431	73	200	220	230	1600	1800		196	119,5		
GT30082UF431	82	190	210	220	1500			202	124,5		
GT30100UF431	100	180	200	220				215	138,5		
GT30125UF431	125	160	180	200				231	142,5		