




4 DELİKLİ ASAE-L TANDEM DİŞLİ POMPA


 HİDROLİK SEMBOL
 HYDRAULIC SYMBOL


Fluid	Mineral or synthetic compatible with the following seals: NBR, FKM, FPM, Nylon			
Kinematic viscosity suggested	Average ambient temp. (°C)	< -10	-10-10	10-35
	VG (cSt = mm²/s)	22	32	46
Optimale kinematic viscosity		VG= 10 cSt - 100 cSt		
Max kinematic viscosity suggested at the start-up		VG= 750 cSt		
Viscosity index suggested	VI > 100	Working temperature -15°C +100°C		
Oil filtering		> 200 bar: 10 µm < 200 bar: 25 µm		
Inlet pressure		-0,3 - 2 bar		



Kod Code	İletim hacmi Displacement	Max. Sürekli Basıncı Max. Continuous pressure	Maks. Aralıklı Basıncı Max. Intermittent Pressure	Maks. Anlık Basıncı Max. Peak Pressure	Maks. Sürekli Hız Max. Continuous Speed	Maks. Aralıklı Hız Max. Intermittent Speed	Min. Hız Min. Speed	A	B	Giriş Inlet	Çıkış Outlet
BD	(cm³/rev)	(100%)(BAR)	(20 sec.max)(BAR)	(6 sec.max)(BAR)	(RPM)	(RPM)	(RPM)	(mm)	(mm)	Ç	Ç
GT300175F831	17	290	315	325	2500	3000	300	182,5	123,5	G1/2"	G1/2"
GT300225F831	22							186,5	126,5		
GT300275F831	27							188,5	126,5		
GT300345F831	34	280	300	310	2200	2800		193,5	128,5	G3/4"	G3/4"
GT300365F831	36							193,5	128,5		
GT300385F831	38							193,5	128,5		
GT300435F831	43	270	290	300	2000	2500		199,5	133		
GT300515F831	51	240	260	280				204,5	134,5		
GT300615F831	61	220	240	250	1800	2000		212,5	138,5	G1 1/4"	G1 1/4"
GT300735F831	73	200	220	230	1500	1800		217,5	141		
GT300825F831	82	190	210	220				223,5	146		
GT301005F831	100	180	200	220				236,5	160		
GT301255F831	125	160	180	200				252,5	164		